

**forede**<sup>®</sup>

**High Pressure Selectable Gallonage Nozzle**

**Model: QLD40/7III-25**



## NOZZLE COMPONENTS



- The Nozzle is workable at both 6 bar and 40 bar;
- Water flow comes from the handle, it could effectively reduce the reaction force;
- Rotation of the bumper enables the selection of the stream patterns (Straight stream, Narrow fog, Wide fog);
- Selectable flow rate between 20–50–100–150 LPM – Flush;
- Made in light weight hard coated anodized aluminium alloy.

## DIMENSION



## TECHNICAL PARAMETER

Model Number	QLD40/7III-25	Rating Flow Rate	20-50-100-150 LPM -Flush @ 6 bar selectable
Rating Working Pressure	6 bar	Max. Flow Rate	400 LPM @ 40 bar
Max. Working Pressure	40 bar	Material	Body: Aluminium Alloy
Jetting Range	23 m @ 6 bar		Slide Valve:Stainless steel
	30 m @ 10 bar		Bumper:Rubber
Max. Jetting Range	35 m @ 40 bar	Inlet	1" BSP Female Thread
Jetting Pattern	Straight Stream- Narrow Fog(60° )-Wide Fog(120° )		

## OPERATION

1. Twist the Bumper to adjust the SS-FOG pattern;
2. Twist the flow adjusting ring to obtain require flow rate;
3. Pull the Trigger and press the locking button to open the Slide Valve;pull the Trigger,locking button and trigger reset, Slider Valve close.



Straight Stream



Narrow Fog (60°)



Wide Fog (120°)



## PERFORMANCE CHART



Range 23m (@6bar) 30m (@10bar) Max.Fog Angle 120°